

## Vaisala HMD60 HMD60 Humidity & Temperature Duct Transmitter

Humidity & Temperature Duct Transmitter		HMD60	1	2	3	4	5	6	7	8	9	10	Price	
1	Probe Length	<b>Standard (25 cm)</b> <i>Short (10cm)</i>	A	B										
2	Output Signal	<b>4 ... 20 mA (loop powered)</b> <b>0 ... 10 V</b> <b>0 ... 5 V</b> <b>1 ... 5 V</b> <b>BACnet/Modbus</b>	1	2	3	4	5							
3	Channel 1	<b>RH (0...100%)</b> <b>Td/f (-40 ...+80°C)</b> <b>A (0 ... 300 g/m<sup>3</sup>)</b> <b>X (0 ... 600 g/kg)</b> <b>Tw (-40 ... +80°C)</b> <b>H (-40 ... +1600 kJ/kg)</b>	A	B	C	D	E	F						
	Special	<i>Define Quantity:</i> <i>Scale:</i>					X							
4	Channel 2	<b>T (-20 ...+80°C)</b> <b>T (-40 ...+80°C)</b>	1	2										
	Special	<i>Define Quantity:</i> <i>Scale:</i>					X							
5	Identity	<b>Vaisala</b>						A						
6	Sensor	<b>Humicap R2</b> <i>Catalytic sensor</i>						1	2					
7	Filter	<b>Stainless Steel Grid</b> <i>Sintered Stainless Steel Filter</i> <i>Sintered Teflon Filter</i>							A	B	C			
8	Bushing 1 (small)	<b>Plugged</b> <b>Cable gland 4...8 mm</b> <i>Conduit fitting NPT1/2"</i>								0	1	2		
9	Bushing 2 (large)	<b>Plugged</b> <i>Cable Gland 6...12 mm</i>									N	A		
10	User Guide	<b>None</b> <i>Multilingual Analog</i> <i>Multilingual Digital</i>										0	1	2
												TOTAL		
Additional information												QTY		
												TOTAL VALUE		

**Selections in bold are included in the prices of the basic versions.**  
*Selections in italic are available at an extra price.*

Example of order code with typical settings:

**HMD60 A 1 A 1 A 1 A 1 N 1**

**Spare Parts**

Stainless Steel Grid  
Sintered Stainless Steel Filter  
Sintered Teflon Filter  
Cable Gland 4...6 mm  
Conduit fitting NPT1/2"

ASM212652SP  
HM46670SP  
DRW244938SP  
254280SP  
210675SP