

Vaisala INTERCAP® Humidity and Temperature Probe HMP63

Vaisala INTERCAP® Humidity and Temperature Probe		HMP63															PRICE	
1	Output signals	0...1 V 0...2.5 V 0...5 V 1 ...5V Scaling for 4..20 mA converter (channel 1 only) Modbus RS485 Interface for Vaisala devices (VDIGI) Modbus with custom address ()	A B C D I M R V X															
2	Measured parameter for channel 1	RS485 RH T (-40 ... +60°C) Td (-40 ... +60°C) Parameter 1 ()	0 1 2 3 X															
3	Measured parameter for channel 2	RS485 or current interface RH T (-40 ... +60°C) Td (-40 ... +60°C) Parameter 2 ()	0 1 2 3 X															
4	Sensor protection	Plastic grid with filter 230727SP Teflon sintered filter 219452SP	A D															
5	Accessories	No accessories Probe holder for Vaisala products (DRW238590SP)	0 2															
6	Humidity sensor	Intericap	A															
7	Probe cable length	No cable 60 °C cable 0.3 m HMP50Z032SP 60 °C cable 3 m HMP50Z300SP 180 °C FEP cable 3m 226902SP																
8	User guide	No user guide Multilingual quick guide	A B															
9	Loop power converter	No converter <i>4...20 mA loop power converter</i>	0 1															
																TOTAL		
																QTY		
																TOTAL VALUE		

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMP63 A 1 2 A 0 A 1 B 0

Accessories:

- UI-CONVERTER-1CB 4 ... 20 mA loop power converter
- 225979 Mounting bracket for converter
- 219690 USB cable for PC connection
- 226067 Probe mounting clamp set, 10 pcs
- 226061 Probe mounting flange
- DRW238590SP Plastic locking bushing (3 pcs) for HMP113 attachment to HM40 indicator