



Temperature probe TMP1
IP68 immersion and steam proof

		Probe type	Probe cable	Sensor type	Filter type	Sensor purge	RS-485 baud rate	Data, Parity, Stop bits	Modbus address	Reserved	Installation accessory	Connection cable
	Order code	TMPX	1	1	A	0						
1	Probe type	TMP1 temperature probe, IP68		1								
2	Cable length	2m cable		A								
		10m cable		B								
3	Sensor type	PT100 (class F0.1 IEC 60751)		1								
4	Filter type	None		A								
5	Reserved	None				0						
6	RS-485 baud rate	1) 19200				A						
		9600				B						
7	Data, Parity, Stop bits	1) 8,N,2						0				
		8,E,1						2				
		8,O,1						4				
8	Probe Modbus address	1) 240							A			
		110							B			
		120							C			
		130							D			
		140							E			
9	Reserved	None								0		
10	Probe mounting accessory	None									0	
		<i>Duct installation kit</i>									A	
		<i>Swagelok for ISO 1/8"</i>									B	
		<i>Swagelok for NPT 1/8"</i>									C	
11	Connection cable	None										0
		<i>1,5m, open ends</i>										1
		<i>10m, open ends</i>										2

1) Factory pre-set, can be changed in the field with a service cable (P/N USB2)

Probe can be connected to INDIGO series of transmitters regardless of the output configuration.

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code with typical settings:

For use with INDIGO transmitters	TMPX	1	A	1	A	0	A	0	A	0	0	0
For use with Modbus RTU	TMPX	1	A	1	A	0	A	0	A	0	0	2

Valid from: February 2021